

ST-4815/ST-4825

Trailer-Mounted Speed Sign

The ST-4815 and ST-4825 are trailer-mounted arrowboards with 15 and 25 lights, respectively. They both feature our single-mast design, wireless V-Touch controller, Stealth Technology and Opti Power lens. Both units combine energy-efficient design and high-quality construction to provide the most reliable and cost-effective arrowboards on the market.



WIRELESS V-TOUCH CONTROLLER

- **Easy-to-read** – 3.75 in (95 mm) pressure-sensitive black and white display screen with intuitive interface
- **Wireless** – eliminates wire harness reducing maintenance and repair costs
- **Simple to operate** – the intuitive point-n-go icons allow you to quickly select arrow patterns/mode
- **Additional functionalities** – lamp diagnostics, settings, battery voltage level, and much more



SINGLE-MAST DESIGN

- Arrowboard protected in travel position – safer to use and more efficient to store and transport
- Low center of gravity reduces wind drag – saving fuel costs
- Quick and easy to set up in tight work zones – saving time
- Angle the arrowboard independently towards traffic – increasing safety

SMART ARROWBOARD

Make your arrowboard part of a Smart Work Zone by adding a Speed-Mac from Ver-Mac. Our innovative Speed-Mac is a portable radar sensor that includes a doppler radar and a modem with GPS. Attaching the Speed-Mac to your arrowboard is a really smart way to get a low-cost speed gathering system and to quickly set up a Smart Work Zone.

- Connect to Ver-Mac's JamLogic software
- Transparently get access to speed data
- Integrate with PCMS to automate messages
- And much more

STEALTH TECHNOLOGY

Cleverly hidden battery compartment
– deter thieves from stealing batteries

Long-lasting sealed batteries – no maintenance required.

ENERGY-EFFICIENT DESIGN

- **OPTI POWER LENS**
Designed to maximize each LED output and utilize less energy.
- **SOLAR PANELS**
Provide maximum solar recharging during all four seasons.
- Both models are designed to run 12 months in most regions without manual charging.
- Various configurations of solar panels and batteries are available to meet your needs.

HIGH-QUALITY CONSTRUCTION

- **Powder coating superior finish** – impact, humidity, salt spray and rust resistant
- **4 leveling jacks** – for stabilization and easy transportation
- **Removable tongue** - saves space for storage
- **Manual lift mechanism** – for a quick deployment
- **Heavy-duty plastic fenders** – for durability and easy replacement
- **Plastic battery box** – to minimize battery corrosion
- **2-in. (51 mm) coupler or 3-in. (76 mm) pintle eye** – for easy towing

SEGMENTS

- Highway construction
- Department of Transportation (DOT)
- City and county
- Utility
- Smart Work Zone

DIMENSIONS & WEIGHT

- Overall length: 135 in. (3429 mm)
- Overall width: 71 in. (1791 mm)
- Operating height: 136 in. (3443 mm)
- Traveling height: 92 in. (2332 mm)
- Weight (approx.): 385 kg (850 lb.)

OPTIONS

- Battery charger
 - Tongue wheel jack
- Other options are available to meet your needs.

Contact us today for more information.

Edmonton | Calgary | Langley | Regina | Saskatoon | Winnipeg
T 800.661.7346 E info@atstraffic.ca

atstraffic.ca | Since 1966

