

KY-3170™ XM / DYMEC 3170™ Series

6 x 4 Port, Managed, Ten Gigabit, Temperature Hardened, ITS, Industrial, Input File, Ethernet Switch with 4- 1/10 GbE Uplinks – Low Power / NSA End Point Certified with ERPSv2



- **6 x RJ45 Gigabit Ports**
- **4x 1GbE /10 GbE SFP Slots**
- **Protection – IP30 / Fanless, Convection Cooled**
- **NSA Network Endpoint Guideline Certified for Console Port Shutdown and Chassis Full Security (Patent Pending)**
- 5 Year / Limited Lifetime Warranty
- Input File / Low Power Industrial Ethernet Switch
- Built for harsh environments & wide temperature ranges
- Edge Computing & Transport Networks
- RSTP, MSTP, ERPS, LACP for Network Redundancy
- QoS CoS / DSCP Advanced Queueing
- Supports IGMP Snooping v1/v2/v3, up to 1024 groups
- DHCP Relay Option 82 Policy for IP address assignment
- SNMP v1/v2c/v3 for network management
- Supports Storm Protection / Broadcast Storm Suppression
- USB storage for configuration-free replacement
- Supports industrial automation protocols Ethernet/IP and Modbus TCP
- Secure File Transfer Protocol (SFTP) & Trivial File Transfer Protocol (TFTP)



Specifications

Technology

- IEEE 802.3 10BaseT
- IEEE 802.3u 100BaseTX
- IEEE 802.3ab 1000BaseT
- IEEE 802.3ae 10GBase over Fiber
- IEEE 802.3x Flow Control
- IEEE 802.3ad/802.1AX LACP
- IEEE 802.1D Spanning Tree Protocol
- IEEE 802.1w Rapid STP

Standards

- IEEE 802.1s Multiple STP
- ITU-T G.8032 / Y.1344 ERPS
- IEEE 802.1Q VLAN Tagging
- IEEE 802.1ad Stacked VLANs
- IEEE 802.1p Class of Service
- IEEE 802.1X Network Authentication
- IEEE 802.1AB LLDP

Processing Type

Store and Forward

Switch Properties

Priority Queues	8 Queues
Jumbo Frame	16000bytes
MAC Table Size	16K
VLAN Table Size	4094
IGMP Group	1024
Packet Buffer	12Mbits

Software Features

Network Redundancy	RSTP, MSTP, G.8032 ERPSv2, Port Trunking with LACP
Security	802.1X, RADIUS, TACACS+, SSL, SSH, ACL*
Management	IPv4, IPv6, Web, Telnet, Serial Console, CLI, SFTP, SNMP v1/v2c/v3, uPnP
Diagnostics	RMON, SNMP Inform/Trap, Syslog, SMTP, Port Mirroring, LLDP, DDM, Fiber & Copper Cable Diagnostics
Configuration	DHCP Server/Client, Relay Option 82, TFTP, SFTP, USB
Filter	802.1Q VLAN, Q-in-Q, IGMP Snooping v1/v2/v3, IGMP Querier, Independent Vlan Learning, MLDv1/v2 Snooping*
Time Sync.	NTP
QoS	CoS, DSCP, WRR/SPQ Queuing, Storm Protection
Industrial Profiles	Ethernet/IP, Modbus TCP

Interfaces

RJ45 Ports	6 x 10/100/1000T(x), auto negotiation speed duplex mode, auto MDI/MDI-X
Fiber Ports	4 x 1/10 GbE SFP Slots
LED Indicators	Per unit: PWR1, Fault, Ring Master, Ring State Ports: Link/Active with highest speed(Green), low speed(Amber)
Button	Multiple function reset button
Serial Console	1 x RS232 in RJ45 connector with console cable, 115.2Kbps, 8N1
Storage	1 x USB 2.0 storage for firmware update, configuration backup, restore, boot up and syslog

Power Requirements

Operation Voltage	12-48 Volts DC
Connection	PCB Golden Finger
Power Consumption	0.67A@24 Volts DC
Protection	Overload Current Protected, Reverse Polarity Protected

Mechanical Construction

Enclosure	Military Grade Steel / Aluminum
Protection Class	IP30
Dimensions	58 x 114 x 205 mm (W x H x D)
Weight	0.87 kg
Mounting	Rack Mounting with Rail Slots

Environmental Limits

Operating Temperature	Extended: -40°C ~ 80°C (-40°F ~ 176°F)
Storage Temperature	-40°C ~ 85°C (40°F ~ 185°F)
Ambient Relative Humidity	5 to 95%, (Non-Condensing)


Regulatory Approvals

Altitude – GB4943.1-2011	0 ~ 5000 Meters
EMI	FCC Part 15 Subpart B Class A CE EN 55032 Class A
EMS	IEC61000-4-2 (ESD) IEC61000-4-3 (RS) IEC61000-4-4 (EFT) IEC61000-4-5 (Surge) IEC61000-4-6 (CS) IEC61000-4-8 (Magnetic Field)
Free Fall	IEC60068-2-32
Shock	IEC60068-2-27
Vibration	IEC60068-2-6
Green	RoHS Compliant
Certifications	UL 60950-1/62368 61000-6-2 / FCC / NEMA TS-2 61000-6-4 / ITUT / IEEE
MTBF MIL-HDBK-217 IEC 62380	>167,000 hours
Warranty	5 Years / Limited Lifetime

Note from DYMEC development.

In a continuing effort of improvement and updated technology, product specifications are subject to change without notice.



Dimensions (unit = mm)



DYMEC 3170 Supports: 2 & 4 Wire LONG RANGE ETHERNET / VDSL2 SFP Modem
 With long reach coverage, high noise immunity, and compact board size, **DYMEC KY-Pro-180-CRD Ruggedized** SFP modem is an ideal upgrade for your Enterprise or Industry applications. Used in Pairs.

VDSL2 – Long Range Ethernet Application (KY-Pro-180-CRD)

MECHANICAL DIMENSIONS (Units in mm)



DYMEC KY-SFP-T

Copper SFP Transceiver – Used to Add Additional RJ-45 Copper Ports to your KY-3170 Series Switch
 Easy to Install & Configure – GUI Selectable

Ordering Information

KY-3170™ XM 6 x 4 Port, Industrial, Managed, 10GbE, ITS Ethernet Switch with 4 x 1 / 10 GbE Uplinks
- 6 x 10/100/1000BaseT(X) + 4 x 1 /10 GbE SFP Slots
- Operating Temperature: -40°C ~ 80°C (-40°F ~ 176°F)

DYMEC 3170™ Series NSA Guideline Certified for Console Port Shutdown and Chassis Full Security

KY-3170™ XM/2 6 x 4 Port, Industrial, Managed, 1 / 10GbE, ITS Ethernet Switch with 4 x 1 / 10 GbE Uplinks (Configured 8 Copper RJ45 Ports)

DYMEC 3170™ Series - 6 x 10/100/1000BaseT(X) + 2 x 10/100/1000 Copper SFP + 2 x 1 /10 GbE SFP Slots
- Operating Temperature: -40°C ~ 80°C (-40°F ~ 176°F)

NSA Guideline Certified for Console Port Shutdown and Chassis Full Security



DYMEC – Temperature Hardened, American Made, Ruggedized, NSA Certified Endpoint, Industrial Ethernet Switches / Routers for SCADA, ITS, Transportation, Automation, Power Utilities, Edge Computing, AI and Industrial Control Systems. Made in USA. TAA Compliant. Uses SFP's / BiDi SFP's / Mini Gbic & VDSL2 Industrial SFP for Long Range Ethernet



⚙️ Service Control

HTTP	<input checked="" type="radio"/> Enable	<input type="radio"/> Disable
HTTPS	<input checked="" type="radio"/> Enable	<input type="radio"/> Disable
SSH	<input checked="" type="radio"/> Enable	<input type="radio"/> Disable
Telnet	<input checked="" type="radio"/> Enable	<input type="radio"/> Disable
Console	<input checked="" type="radio"/> Enable	<input type="radio"/> Disable
Reset-Button	<input checked="" type="radio"/> Enable	<input type="radio"/> Disable

Apply